

Show Floor

This super glossy floor is perfect for special events, commercials and fashion promotions. This high shine floor adds just the right sparkle to any venue. Show Floor is not designed for heavy traffic or permanent installation. It is sold by the full roll only, cut footage is not available.

Composition:

Constructed in multiple layers; consisting of poly vinyl chloride, resin, plasticizers and pigments

Nominal thickness:

0.08" (2.0 mm)

Co-calendared wear layer: .032" (0.8 mm)

Middle and backing layers: .048" (1.2 mm)

Roll Size:

72" (1,830 mm) wide x 60' (18.28 m) long

Weight:

275 lbs (125 kg) per roll

Colors Available:

Black, White and Red

Flame Spread:

ASTM E684-97 Class 1 per NFPA 253

Smoke Density:

ASTM E662/NFPA 258

Abrasion Resistance:

ASTM D3884—Net weight loss after 1000 revolutions: 0.54%

Static Load Limit:

ASTM F970-87—Residual compression after exposure to a load of 125 lbs. /24 hours: .003" (Please note: ASTM F 970 is a Pass/Fail test. To pass, residual indentation must be less than .007". This test does not establish load limits.)

Flexibility:

ASTM F137—Passes

Floor Speed:

Medium

Product Numbers

300 74035 7200 - Black 6'-0" x 60' (1.83 m x 18.29 m)

300 74030 7200 - White 6'-0" x 60' (1.83 m x 18.29 m)

300 74036 7200 - Red 6'-0" x 60' (1.83 m x 18.29 m)